

Bathroom drier **ECORA**

Instruction for use

Product description:

ECORA bathroom drier (TPK) consists of built-in tempering unit NOMATERM (type 1). Sanded NOMATERM unit is put in the aluminum frame and from the back side it is protected by insulation material covered with aluminum foil and aluminum plate. **ECORA** bathroom drier belongs to 1st class appliances. There is inner thermostat built-in TPK to prevent overheating in case that something falls onto heating element. Networking is through cable with contact plug with integrated switch (type „v) or with integrated room thermostat (type „r“). Standard painting of aluminum frame is anodized coating.

Application:

ECORA bathroom drier is made for heating or drying in bathrooms.

Basic technical specification:

Versions of TPK are made according to technical conditions of tempering unit NOMATERM with its input 10 W/dm² of working area.

ECORA bathroom drier is made for 100 °C maximum surface temperature. TPK is designated for alternate current (AC), voltage 230 V.

| | | |
|-------------------|----------------------|---------------|
| Size : | TPK 200 v | 840 x 390 mm, |
| | TPK 200 r | 840 x 390 mm, |
| | TPK 400 v | 890 x 530 mm, |
| | TPK 400 r | 890 x 530 mm |
| Input | 10 W/dm ² | |
| Voltage | 230 V, 50 Hz | |
| Protection | IP 44 | |

Installation :

Installation in bathrooms must be done according to ČSN 332135 part 1. Product can be installed in 2nd or 3rd zone (except bath ground plan).

Maintenance and repair:

Possible maintenance of product is cleaning dusted surface with the vacuum cleaner or wet sponge. Do not use any detergent or dissolution reagent to clean working area of the **ECORA** panel. Tempering unit NOMATERM mustn't be mechanical damaged during installation or operation. In case of cable damage it must be replaced with another by producer, service engineer or certified person. Panel must be cold and completely disconnected during maintenance. Only producer could make any repairs.

Certificate of guarantee:

Guaranty time for **ECORA** bathroom drier operation is 24 months from sell-by date. Product will be free repaired by manufacturer in functional defect incidence not caused by user during guaranty time. Guarantee is not granted to any color changes of workable surface or any mechanical damage caused by misuse.

Type:

SAKUTUSI 39131 Dražice 256, Czech Republic

Date:

tel.,fax: +420 381 239 027